

100% Money Back
Guarantee

Vendor:Citrix

Exam Code:1Y0-A28

Exam Name:Implementing NetScaler 10 for
Networking and Traffic Optimization

Version:Demo

QUESTION 1

A network engineer needs to upgrade both appliances of a High Availability (HA) pair. In which order should the network engineer upgrade the appliances?

- A. Disable high availability and upgrade one node at a time.
- B. Upgrade the primary node first without disabling high availability.
- C. Upgrade the secondary node first without disabling high availability.
- D. Perform the upgrade simultaneously without disabling high availability.

Correct Answer: C

QUESTION 2

Scenario: A network engineer plans to configure an Active Directory Server as the default authentication for a NetScaler deployment and provide users with the option to change their password if it is expired. Which two actions should the engineer take to configure this authentication requirement on the NetScaler system? (Choose two.)

- A. Configure a pre-authentication policy.
- B. Select security type as SSL on Authentication policy.
- C. Configure Authentication server with SSO name attribute.
- D. Configure Authentication server with allow Password change option.

Correct Answer: BD

QUESTION 3

Scenario: A network engineer deployed a new NetScaler MPX appliance on the network and all interfaces are connected to the core switch. The network engineer notices the CPU utilization has become very high on the switch since the NetScaler deployment.

Which two actions could the engineer perform on the NetScaler to resolve this issue? (Choose two.)

- A. Configure VMAC
- B. Utilize static routing
- C. Configure a channel
- D. Connect a single interface only

Correct Answer: CD

QUESTION 4

Scenario: An engineer has configured a virtual server that users access using HTTP port 80. The web application also uses TCP port 81 and 8080 for non-user access. The engineer would like to prevent users from connecting to web servers if any of the ports go down. How should the engineer set this configuration to ensure service availability?

- A. Increase the monitor threshold.
- B. Lower the server timeout value.
- C. Create additional virtual servers for ports 81 and 8080.
- D. Create monitors for ports 81 and 8080, and bind to the service or service group.

Correct Answer: D

QUESTION 5

Company policy states that all passwords should travel the network in encrypted packets except SNMP. Which command should the network engineer execute to comply with this policy?

- A. `set ns ip 10.20.30.40 -ssh disabled -telnet disabled -gui enabled`
- B. `set ns ip 10.20.30.40 -telnet disabled -gui secureonly -ftp disabled`
- C. `set ns ip 10.20.30.40 -mgmtaccess disabled -restrictaccess enabled`
- D. `set ns ip 10.20.30.40 -gui secureonly -ssh enabled -restrictaccess enabled`

Correct Answer: B

QUESTION 6

Scenario: A network engineer has configured GSLB for a multisite environment. All GSLB services show as UP with an UP MEP status.

The engineer has observed that DNS queries are directed to the SNIP of the NetScaler; however, no DNS response is being received. How can the engineer resolve this issue?

- A. Add an ADNS service on the SNIP.
- B. Change the DNS delegation to the NSIP.
- C. Create a load balancing virtual server for DNS.
- D. Select the "Send all "active" service IPs\\' in response (MIR)" option.

Correct Answer: A

QUESTION 7

The purpose of pre-fetch in integrated caching is to automatically _____. (Choose the correct option to complete the sentence.)

- A. refresh a cached object before expiring
- B. fetch objects from the forwarding cache before expiring
- C. retrieve all objects on a published website after a policy is applied
- D. retrieve an object in the expression from a website after a policy is applied

Correct Answer: A

QUESTION 8

Scenario: The network engineer is unable to access a specific SSL site through the NetScaler. While reviewing traces on the NetScaler, the network engineer noticed "Handshake" failures from the server. These handshake failures could be the result of the virtual server _____. (Choose the correct option to complete the sentence.)

- A. only allowing TLS
- B. not allowing SSLv3
- C. not allowing correct ciphers
- D. configured to demand client authentication

Correct Answer: C

QUESTION 9

Scenario: Primary NetScaler (NS1) is licensed for 10000 Maximum ICA users and 305 Access Gateway users. Secondary NetScaler (NS2) is licensed for 10000 Maximum ICA users and five Access Gateway users.

From where and which command should a network engineer run to display diagnostics on the licenses?

- A. From the shell, run `view license`.
- B. From the shell, run `more /var/log/license.log`.
- C. From the command-line interface, run `show license`.
- D. From the command-line interface, run `cat /var/log/license.log`.

Correct Answer: B

QUESTION 10

Scenario: A network engineer needs to implement high availability (HA) for a pair of NetScaler appliances. The existing appliance was recently restarted and the new appliance has been rack mounted and turned on for several weeks waiting to be configured. The engineer needs to create an HA pair, but is concerned that his original appliance will get

erased when the HA pair is created.

Which two tasks could the engineer do before the creation of the HA pair to ensure that the existing unit stays the main appliance? (Choose two.)

- A. Set StayPrimary on the existing node.
- B. Configure StaySecondary on the new node.
- C. Enable HA Sync before adding the second node.
- D. Create a Route Monitor to ensure proper synchronization.
- E. Ensure that INC mode is enabled during creation of HA Pair.

Correct Answer: AB

QUESTION 11

Scenario: A network engineer suspects that there is a duplex mismatch in the network configuration. The NSIP address is 10.10.1.206. How can the administrator verify the configuration in this scenario?

- A. Run the `netstat -r` command.
- B. Run the `show IP 10.10.1.206` command.
- C. Run the `start nstrace -level 10` command.
- D. Check for the interface configuration in the GUI.

Correct Answer: D

QUESTION 12

Scenario: A network engineer is going to roll out an upgrade from a 9.x version on a standalone NetScaler appliance using the command-line interface.

Which two items does the engineer need to download before proceeding with the upgrade? (Choose two.)

- A. SSL Certificates Files
- B. NetScaler Firmware File
- C. NetScaler Configuration file
- D. NetScaler Documentation File

Correct Answer: BD

To Read the [Whole Q&As](#), please purchase the [Complete Version](#) from [Our website](#).

Try our product !

100% Guaranteed Success

100% Money Back Guarantee

365 Days Free Update

Instant Download After Purchase

24x7 Customer Support

Average 99.9% Success Rate

More than 800,000 Satisfied Customers Worldwide

Multi-Platform capabilities - [Windows](#), [Mac](#), [Android](#), [iPhone](#), [iPod](#), [iPad](#), [Kindle](#)

Need Help

Please provide as much detail as possible so we can best assist you.

To update a previously submitted ticket:



| | | |
|---|---|--|
|  <p>One Year Free Update Free update is available within One Year after your purchase. After One Year, you will get 50% discounts for updating. And we are proud to boast a 24/7 efficient Customer Support system via Email.</p> |  <p>Money Back Guarantee To ensure that you are spending on quality products, we provide 100% money back guarantee for 30 days from the date of purchase.</p> |  <p>Security & Privacy We respect customer privacy. We use McAfee's security service to provide you with utmost security for your personal information & peace of mind.</p> |
|---|---|--|

Any charges made through this site will appear as Global Simulators Limited.

All trademarks are the property of their respective owners.