100% Money Back Guarantee

Vendor: Zend-Technologies

Exam Code: 200-500

Exam Name: Zend PHP 5 Certification

Version: Demo

You work for a shared hosting provider, and your supervisor asks you to disable user scripts to dynamically load PHP extensions using the dl() function. How can you do this? (Choose 2)

A. Setenable_dl to Off in the server's php.ini configuration file.

B. Add dl to the current value ofdisable_functions in the server's php.ini configuration file.

C. Add dl to the current value ofdisable_classes in the server's php.ini configuration file.

D. Write a custom function calleddl(), save it under the name prepend.inc and then set the auto_prepend_file directive to prepend.inc in php.ini.

Answer: A,B

QUESTION NO: 2

Which of the following statements is NOT true?

- a) Class constants are public
- b) Class constants are being inherited
- c) Class constants can omit initialization (default to NULL)
- d) Class constants can be initialized by consts
- A. a)
- B. b)
- C. c)
- D. d)

Answer: C

QUESTION NO: 3

Type hinting in PHP allows the identification of the following variable types: (Choose 2)

- A. String
- B. Integer
- C. Array
- D. Any class or interface type

Answer: C,D

QUESTION NO: 4

How many elements does the \$matches array contain after the following function call is performed?

preg_match('/^(\d{1,2}([a-z]+))(?:\s*)\S+ (?=200[0-9])/', '21st March 2006', \$matches);

A. 1

- B. 2
- C. 3
- D. 4

Answer: C

QUESTION NO: 5

Given the following code, what will be the value of \$a?

\$a = array('a', 'b'); array_push(\$a, array(1, 2));

A. array('a', 'b', 1, 2) B. array(1, 2, 'a', 'b') C. array(array(1, 2), 'a', 'b') D. None of the above

Answer: D

QUESTION NO: 6

Which of the following filtering techniques prevents cross-site scripting (XSS) vulnerabilities?

- A. Strip all occurrences of the string script.
- B. Strip all occurrences of the stringjavascript.
- C. Enablemagic_quotes_gpc.
- D. None of the above.

Answer: D

QUESTION NO: 7

Identify the security vulnerability in the following example:

```
1 <?php
2 echo "Welcome, {$_POST['name']}.";
3 ?>
A. SQL Injection
```

- B. Cross-Site Scripting
- C. Remote Code Injection
- D. None of the above

Answer: B

QUESTION NO: 8

How many times will the function counter() be executed in the following code?

```
functioncounter($start, &$stop)
{
    if($stop > $start)
    {
        return;
    } counter($start--, ++$stop);
    }
    $start = 5;
    $stop = 2;
    counter($start, $stop);
    A. 3
    B. 4
    C. 5
    D. 6
```

```
Answer: C
```

QUESTION NO: 9

When a class is defined as final it:

- A. Can no longer be extended by other classes.
- B. Means methods in the class are not over-loadable.
- C. Cannot be defined as such, final is only applicable to object methods.
- D. Is no longeriteratable.

Answer: A

QUESTION NO: 10

Which parts of the text are matched in the following regular expression?

```
1 <?php
2 $text = <<<EOT
3 The big bang bonged under the bung.
4 EOT;
5
6 preg_match_all('@b.n?g@', $text, $matches);
7 ?>
```

- A. bang bong bungB. bang bonged bungC. big bang bong bung
- D. big bang bung

Answer: C

QUESTION NO: 11

Which of the following can be registered as entry points with a SoapServer instance (choose 3)

- A. A single function
- B. A single method from a class
- C. Multiple functions at once
- D. All methods from a class
- E. All classes defined in a script

Answer: A,C,D

QUESTION NO: 12

What DOMElement method should be used to check for availability of a non-namespaced attribute?

- A. getAttributeNS()
- B. getAttribute()
- C. hasAttribute()

D. hasAttributeNS()

Answer: C

QUESTION NO: 13

Which of the following data types is implicitly passed by reference in PHP 5 while it is passed by value in PHP 4?

- A. Class
- B. String
- C. Object
- D. Array

Answer: C

QUESTION NO: 14

What is the content of \$c after the following code has executed?

\$a = 2; \$b = 3; \$c = (\$a++ * ++\$b); A. 0 B. 5 C. 8 D. 4

QUESTION NO: 15

Which options do you have in PHP to set the expiry date of a session?

- A. Set thesession.duration directive in php.ini
- B. Set session cookie expiry date locally viasession_set_cookie_params()
- C. Set session expiry date locally viasession_cache_expire()
- D. None of the above

Answer: D

A script residing at http://example.com/phpcert/cookies.php contains the following code:

```
1 <?php
2 setcookie('name1', 'value1', time() + 60*60*24, '/');
3 setcookie('name1', 'value2');
4 ?>
```

The web browser is configured to accept all cookies. How many cookies will be set by this script?

A. 0 B. 1

C. 2

D. 3

Answer: C

QUESTION NO: 17

You analyze the code of a collegue and see, it uses the function strcasecmp. You try it out to see what it does and use the following function call: strcasecmp('hello my dear!', 'Hello my DEAR!'); The function call returns "0". What does that mean?

- A. String 1 is less than string 2.
- B. The strings are considered equal.
- C. String 2 is less than string 1.
- D. The strings have equal length.

Answer: B

QUESTION NO: 18

What is the output of the following script?

1 <?php 2 class a 3 { 4 public \$val; 5 } 6

```
7 function renderVal (a $a)
8 {
9 if ($a) {
10 echo $a->val;
11 }
12 }
13
14 renderVal (null);
15 ?>
A. A syntax error in the function declaration line
B. An error, because null is not an instance of 'a'
```

- C. Nothing, because a null value is being passed torenderVal()
- D. NULL

Answer: B

QUESTION NO: 19

REST is a(n) ...

- A. Web service protocol similar to SOAP with a strict XML schema.
- B. Principle to exchange information using XML and HTTP.
- C. API to get information from social networking sites.

Answer: B

QUESTION NO: 20

What is the output of the following code?

echo0x33, 'monkeys sit on ', 011, ' trees.';

- A. 33 monkeys sit on 11 trees.
- B. 51 monkeys sit on 9 trees.
- C. monkeys sit on trees.
- D. 0x33 monkeys sit on 011 trees.

Answer: B

When checking whether two English words are pronounced alike, which function should be used for the best possible result?

- A. levenshtein()
- B. metaphone()
- C. similar_text()
- D. soundex()

Answer: B

QUESTION NO: 22

Given the following code, what is correct?

```
functionf(stdClass &$x = NULL) { $x = 42;
}
$z = new stdClass;
f($z);
var_dump($z);
```

- A. Error:Typehints cannot be NULL
- B. Error: Typehints cannot be references
- C. Result is NULL
- D. Result is object of typestdClass
- E. Result is 42

Answer: E

QUESTION NO: 23

What is the maximum size of the VARCHAR column type?

- A. 255 Bytes
- B. 255 Characters
- C. 512 Bytes
- D. 512 Characters
- E. No Limit

Answer: B

What is the output of the following code?

```
<code> classtest
{ public$value =
0; functiontest() {
$this->value = 1;
} function __construct() {
$this->value = 2;
}}
$object = new test();
echo$object->value;
A. 2
B. 1
C. 0
```

- D. 3
- E. No Output, PHP will generate an error message.

Answer: A

QUESTION NO: 25

Transactions can be used to: (Choose 2)

- A. Recover from errors in case of a power outage or a failure in the SQL connection
- B. Ensure that the data is properly formatted
- C. Ensure that either all statements are performed properly, or that none of them are.
- D. Recover from user errors

Answer: A,C

QUESTION NO: 26

Which piece of code will return the ASCII value of a character?

A. (int)'t';
B. ord('t');
C. to_ascii('t');
D. chr('t');

Answer: B

QUESTION NO: 27

Which of the following data types cannot be directly manipulated by the client?

- A. Cookie Data
- B. Session Data
- C. Remote IP Address
- D. User Agent

Answer: B

QUESTION NO: 28

An HTML form contains this form element:

<input type="image" name="myImage" src="image.png" /> The user clicks on the image to submit the form. How can you now access the relative coordinates of the mouse click?

- A. \$_IMAGE['myImage']['x'] and \$_IMAGE['myImage']['y']
- B. \$_POST['myImage']['x'] and \$_POST['myImage']['x']
- C. \$_POST['myImage.x'] and \$_POST['myImage.y']
- D. \$_POST['myImage_x'] and \$_POST['myImage_y']

Answer: D

QUESTION NO: 29

Which of the following statements is correct?

- A. Interfaces can extend only one interface
- B. Interfaces can extend more than one interface
- C. Interfaces can inherit a method from different interfaces
- D. Interfaces canredeclare inherited methods

Answer: B

QUESTION NO: 30

.You are creating an application that generates invoices in a variety of formats, including PDF, ODS and HTML. Each of these formats is represented as a PHP class in your application. While some of the operations can be performed on all of the different formats (such as saving and loading), other operations may be specific to one or two of the formats (such as setting as read only). Which design pattern should you use for this application?

- A. Adapter
- B. Factory
- C. MVC
- D. Singleton

Answer: B

QUESTION NO: 31

The following form is loaded in a browser and submitted, with the checkbox activated: <form method="post"> <input type="checkbox" name="accept"> <form>

In the server-side PHP code to deal with the form data, what is the value of \$_POST['accept']?

- A. accept
- B. ok
- C. true
- D. on

Answer: D

QUESTION NO: 32

Which methods can be used to overload object properties? (Choose 2)

A. set(), get()
B. __set(), __get()
C. __put(), __receive(), __exists()
D. set(), get(), isset()
E. isset(), unset()

Answer: B,E

.What super-global should be used to access information about uploaded files via a POST request?

- A. \$_SERVER
- B. \$_ENV
- C. \$_POST
- D. \$_FILES
- E. \$_GET

Answer: D

QUESTION NO: 34

What is the function of backtick (`) characters in PHP?

- A. Same as single-quotes, used to enclose strings.
- B. Escape operators.
- C. No special meaning.
- D. Execute the enclosed string as a command.
- E. Error control operators.

Answer: D

QUESTION NO: 35

Which constant must be passed as the second argument to htmlentities() to convert single quotes () to HTML entities?

- A. TRUE
- B. FALSE
- C. ENT_QUOTES
- D. ENT_NOQUOTES
- E. ENT_COMPAT

Answer: C

QUESTION NO: 36

You want to run the following PHP 4 code with PHP 5. In the following example, which access modifier in PHP 5 is equivalent to "var"?

classTest {

var\$tester;

}

- A. protected
- B. invisible
- C. public
- D. private
- E. outofscope

Answer: C

QUESTION NO: 37

Which of the listed changes would you make to the following PHP 4 code in order to make it most compliant with PHP 5? (Choose 2)

```
<?php
classCar
{ var$mode
l;
functionCar($model) {
$this->model = $model;
} function toString() {
return"I drive a $this->model.";
}}
$c = new Car('Dodge');
echo$c->toString();
?>
```

A. Changevar to public or private

- B. Change function Car tofunction_construct
- C. Change "I drive a \$this->model." to "I drive a {\$this->model}."
- D. Change functiontoString()to static function toString()

Answer: A,B

QUESTION NO: 38

Which of the following statements about PHP is true? (Choose 3)

a) A final class can be derived.

- b) A final class may be instantiated.
- c) A class with a final function may be derived.
- d) Static functions can be final.
- e) Properties can be final.
- A. a)
- B. b)
- C. c)
- D. d)
- E. e)

Answer: B,C,D

QUESTION NO: 39

Webservicesare primarily meant to support

- A. business-to-business communication
- B. machine-to-machine interaction
- C. improved accessibility for websites

Answer: B

QUESTION NO: 40

What is the result of the following bitwise operation in PHP?

1 ^ 2

A. 1

В. З

- C. 2
- D. 4

Answer: B

QUESTION NO: 41

You want to allow your users to submit HTML code in a form, which will then be displayed as real code and not affect your site layout. Which function do you apply to the text, when displaying it? (Choose 2)

A. strip_tags()B. htmlentities()C. htmltidy()D. htmlspecialchars()E. showhtml()

Answer: B,D

QUESTION NO: 42

When working with the MVC paradigma, the business logic should be implemented in which of the following components?

- A. Model
- B. View
- C. Controller

Answer: A

QUESTION NO: 43

What function is used to retrieve all available information about a symbolic link?

- A. symlink()
- B. stat()
- C. fstat()
- D. lstat()
- E. readlink()

Answer: D

QUESTION NO: 44

What is the return value of the following code?

strpos("me myself and I", "m", 2)

A. 2

- B. 3
- C. 4
- D. 0

E. 1

Answer: B

QUESTION NO: 45

What is the output of the following code?

\$first = "second"; \$second = "first"; echo\$\$\$first;

A. first B. second C. an empty string D. an error

Answer: B

QUESTION NO: 46

One common security risk is exposing error messages directly in the browser. Which PHP configuration directive can be disabled to prevent this?

- A. html_display
- B. error_reporting
- C. display_errors
- D. error_log
- E. ignore_repeated_errors

Answer: C

QUESTION NO: 47

What is the error in the following declaration of a static class method?

```
1 <?php
2 class car {
3 static $speeds = array(
4 'fast',
5 'slow',
<u>6 'medium',</u>
```

```
7 );
8
9 static function getSpeeds()
10 {
11 return $this->speeds;
12 }
13 }
14 ?>
```

A. Static methods must not return a value.

B. The use of \$this from within static methods is not possible.

- C. Static methods need the method keyword instead of the function keyword.
- D. There is no static keyword in PHP.

Answer: B

QUESTION NO: 48

Would the following code catch a parse error?

```
try{
echo$label
} catch (Exception $e) {
echo$e->getMessage();
}
```

A. Yes B. No

Answer: B

QUESTION NO: 49

What is the difference between isset() and other is_*() functions (is_alpha(), is_number(), etc.)?

A. isset() is a function call and is_*() are not function calls
B. is_*() are language constructs andisset() is not a language construct
C. c)isset() is a language construct and is_*() are not language constructs
D. d) is_*() return a value whereasisset() does not

Answer: C

What function should be used to escape command line arguments that are passed to commands executed from PHP?

- A. addslashes()
- B. quotemeta()
- C. escapeshellarg()
- D. escapeshellcmd()
- E. passthru()

Answer: C

QUESTION NO: 51

\$_SERVER consists of data provided by the web server and is therefore trustworthy.

- A. TRUE
- B. FALSE

Answer: B

QUESTION NO: 52

What is the name of the PHP function used to automatically load non-yet defined classes?

- A. autoload()
- B. __autoload()
- C. __catch()
- D. load()
- E. loadClass()

Answer: B

QUESTION NO: 53

After executing a SELECT query on a database server,

- A. All data is immediately transmitted to PHP
- B. All data will be transmitted on-demand to PHP
- C. None of the above

Answer: A,B

QUESTION NO: 54

Which of the following are valid identifiers (Choose 3)

A. function4You() { }
B. function _4You() { }
C. functionobject() { }
D. \$1 = "Hello";
E. \$_1 = "Hello World";

Answer: B,C,E

QUESTION NO: 55

What is the output of the following code?

```
1 <?php
2 for ($i = 0; $i < 1.02; $i += 0.17) {
3 $a[$i] = $i;
4 }
5 echo count($a);
6 ?>
A. 0
B. 1
C. 2
D. 6
E. 7
```

Answer: B

QUESTION NO: 56

Transactions are used to:

- A. guarantee high performance
- B. secure data consistency
- C. secure access to the database
- D. reduce the database server overhead

E. reduce code size in PHP

Answer: B

QUESTION NO: 57

What piece of code would you use to obtain an array of response headers for a given URL, indexed by their respective names?

- A. get_headers(\$url);
- B. get_header(\$url);
- C. stream_context_get_headers(\$url);
- D. get_headers(\$url, 1);
- E. get_headers(\$url, ASSOC_HEADERS);

Answer: D

QUESTION NO: 58

Some databases support the LIMIT clause. It is a method to ensure that ...

- A. only certain rows are deleted in DELETE queries.
- B. only a defined subset of rowsare read in SELECT queries.
- C. only certain users can access the database.

Answer: B

QUESTION NO: 59

What is the output of the following code?

printf('%4\$d %2\$s sit on 2 trees and eat %3\$3.2f %1\$s', "bananas", "monkeys", 9, 99);

- A. %4\$d %2\$s sit on 2 trees and eat %3\$3.2f %1\$s
- B. 99 monkeys sit on 2 trees and eat 9.00 bananas
- C. Monkeys Bananas sit on 2 trees and eat 9 99
- D. 9 monkeys sit on 2 trees and eat 99 bananas

Answer: B

Given the default PHP configuration, how can all of the parameters provided via GET be accessed in a form of a string?

A. \$_GET['ALL'] B. \$_SERVER['QUERY'] C. \$_SERVER['QUERY_STRING'] D. \$_ENV['QUERY'] E. \$QUERY_STRING

Answer: C

QUESTION NO: 61

Given the default PHP configuration, how can all of the parameters provided via GET be accessed in a form of a string?

A. \$_GET['ALL']
B. \$_SERVER['QUERY']
C. \$_SERVER['QUERY_STRING']
D. \$_ENV['QUERY']
E. \$QUERY_STRING

Answer: C

QUESTION NO: 62

How to read a single line, no matter how long from an file opened in the example below?

\$fp = fopen("my_file.txt", "w");

- A. fgets(\$fp); B. fgets(\$fp, -1); C. fread(\$fp, 1024); D. fgetss(\$fp);
- E. None of the above

Answer: D

QUESTION NO: 63

Which of the following statements are NOT true?

- A. SimpleXML allows removal of attributes.
- B. SimpleXML allows addition of new attributes.
- C. SimpleXML allows removal of nodes.
- D. SimpleXML allows addition of new nodes.
- E. None of the above

Answer: E

QUESTION NO: 64

Which of the following statements are correct? (Choose 2)

- A. It is possible to specify more than one autoload function
- B. __autoload receives the missing class name all lowercased
- C. __autoload is being called for missing interfaces
- D. Inside __autoload missing classes trigger autoload

Answer: C,D

QUESTION NO: 65

How many elements does the array \$pieces contain after the following piece of code has been executed?

\$pieces = explode("/", "///");
A. 0

B. 3

C. 4

D. 5

Answer: C

QUESTION NO: 66

What does the _____FILE___constant contain?

- A. The filename of the current script.
- B. The full path to the current script.

- C. The URL of the request made.
- D. The path to the main script.

Answer: B

QUESTION NO: 67

You want to parse a URL into its single parts. Which function do you choose?

- A. parse_url()
- B. url_parse()
- C. get_url_parts()
- D. geturlparts()

Answer: A

QUESTION NO: 68

How can a SimpleXML object be converted to a DOM object?

- A. dom_import_simplexml()
- B. dom_export_simplexml()
- C. simplexml_import_dom()
- D. SimpleXML2Dom()
- E. None of the above.

Answer: A

QUESTION NO: 69

What PHP function can be used to remove a local file?

- A. A)rmdir()
- B. B)unlink()
- C. C)rm()
- D. D)delete()
- E. E)delete_file()

Answer: B

What DOM method is used to load HTML files?

A. load()

- B. loadXML()
- C. loadHTML()
- D. loadHTMLFile()

Answer: D

QUESTION NO: 71

What is the output of the following script?

```
1 <?php
2 function fibonacci (\$x1 = 0, \$x2 = 1)
3 {
4 \text{sresult} = \text{sx1} + \text{sx2};
5 $x1 = $x2;
6 $x2 = $result;
7
8 return $result;
9}
10
11 for (\$i = 0; \$i < 10; \$i++) {
12 echo fibonacci() . ',';
13 }
14 ?>
A. An error
B. 1,1,1,1,1,1,1,1,1,1,1,
C. 1,1,2,3,5,8,13,21,34,55,
D. Nothing
```

Answer: B

QUESTION NO: 72

What will be the result of the following operation?

```
array_combine(array("A","B","C"), array(1,2,3));
```

A. array("A","B",C",1,2,3) B. array(1,2,3,"A","B",C") C. array("A"=>1,"B"=>2,"C"=>3) D. array(1=>"A",2=>"B",3=>"C") E. array(1,2,3)

Answer: C

QUESTION NO: 73

Which of the following functions can help prevent session fixation vulnerabilities?

- A. magic_quotes_gpc()
- B. strip_tags()
- C. addslashes()
- D. session_regenerate_id()

Answer: D

QUESTION NO: 74

How can you determine if magic_quotes_gpc is enabled? (Choose 2)

- A. Use theget_magic_quotes() function.
- B. Using theget_magic_quotes_runtime() function.
- C. Use theget_magic_quotes_gpc() function.
- D. Usingini_get('magic_quotes_gpc').
- E. Usingini_get('magic_quotes').

Answer: A,D

QUESTION NO: 75

You want to present the following formatted number: "999.000.000,00". Which function call is correct?

- A. printformat_number(99900000);
- B. printnumber_format(99900000);
- C. printnumber_format(999000000, 2, ',', '.');
- D. printnumber_format(999000000, 2);
- E. print_number(999000000, 2, ',', '.')

Answer: C

QUESTION NO: 76

What function returns the filename component of the file's path:

A. dirname() realpath() B. basename() C. pathinfo() D. parse_url()

Answer: B

QUESTION NO: 77

Which of the following are valid SoapClient calls? (Choose 2)

- A. \$client = newSoapClient("weather.wsdl");
- B. \$client = newSoapClient;
- C. \$client = newSoapClient(null, array("location" =>
- "http://example.com/weather", "uri" => "http://test-uri.com/"));
- D. \$client = newSoapClient(null, array());

Answer: A,C

QUESTION NO: 78

After performing the following operations:

```
$a = array('a', 'b', 'c');
$a = array_keys(array_flip($a));
What will be the value of $a?
```

A. array('c', 'b', 'a') B. array(2, 1, 0) C. array('a', 'b', 'c') D. None of the above

Answer: C

Which of the following statements about exceptions are correct? (Choose 2)

- A. you can only throw classes derived from Exception
- B. a try block can have multiple catch blocks
- C. a try block must not be followed by a catch block
- D. try blocks cannot contain nested try blocks

Answer: A,B

QUESTION NO: 80

After executing a query on a database server, PHP offers several functions to read the resulting lines, such as mysqli_fetch_assoc, pg_fetch_row, oci_fetch,etc.). If such functions do not return any rows, it means: (Choose 2)

- A. a SELECT statement returned no rows
- B. the transaction has been rolled back
- C. the connection to the database server was disconnected during query execution
- D. the query was too slow to execute

Answer: A,C

QUESTION NO: 81

An unbuffered query will: (Choose 2)

- A. Return the first data faster
- B. Return all data faster
- C. Free connection faster for others scripts to use
- D. Use less memory

Answer: A,D

QUESTION NO: 82

What parsing methodology is utilized by the SimpleXML extension?

- A. SAX
- B. DOM
- C. XPath

D. Push/Pull Approach

E. Expat

Answer: B

QUESTION NO: 83

Which of the following is NOT possible using reflection?

- A. Analysing of nearly any aspect of classes and interfaces
- B. Analysing of nearly any aspect of functions
- C. Adding class methods
- D. Implement dynamic construction (new with variable class name)

Answer: C

QUESTION NO: 84

Given the following two functions, what statement is correct?

```
functiondynamicNew($name) {
returnnew $name;
}
functionreflectionNew($name) {
$r = new ReflectionClass($name);
return$r->newInstanceArgs();
}
```

A. Both functions do the sameB. dynamicNew() results in a parse error, reflectionNew() works

Answer: B

QUESTION NO: 85

Which string will be returned by the following function call?

```
$test = '/etc/conf.d/wireless';
substr($test, strrpos($test, '/'));
```

A. ""

- B. "/wireless"
- C. "wireless"
- D. "/conf.d/wireless"
- E. "/etc"

Answer: B

QUESTION NO: 86

Which of the following statements about Reflection are correct? (Choose 2)

- A. Since 5.1 reflection is an extension that can be disabled
- B. Reflection is present in any installation of PHP 5 or later
- C. Reflection only allowsto reflect on built-in classes
- D. Built-in classes can be reflected on command line usingphp -rc <classname>

Answer: A,D

QUESTION NO: 87

Which PHP function retrieves a list of HTTP headers that have been sent as part of the HTTP response or are ready to be sent?

- A. header()
- B. headers()
- C. headers_list()
- D. headers_sent()

Answer: C

QUESTION NO: 88

In a shared hosting environment, session data can be read by PHP scripts written by any user. How can you prevent this?

- A. Store session data in a different location withsession.save_path
- B. Store session data in a database.
- C. Enablesafe_mode.
- D. Set session.name to something unique.

Answer: B

Which is the most secure approach for handling dynamic data in SQL queries?

A. Useaddslashes().

B. Enablemagic_quotes_gpc.

C. Use prepared statements if supported by the database library, data-specific escaping functions otherwise.

D. Use stored procedures.

Answer: C

QUESTION NO: 90

When PHP is running on a command line, what super-global will contain the command line arguments specified?

A. \$_SERVER B. \$_ENV C. \$GLOBALS D. \$_POST E. \$ ARGV

Answer: A

QUESTION NO: 91

Which of the following did not result in an output error in PHP 4 but does in PHP 5?

- A. Using 'var' as an access modifier.
- B. Assigning a new object instance to \$this in a constructor.
- C. Passing an object by-reference.
- D. Passing an object by-value.

Answer: B

QUESTION NO: 92

How many elements does the array \$matches from the following code contain?

To Read the Whole Q&As, please purchase the Complete Version from Our website.

Trying our product !

- ★ 100% Guaranteed Success
- ★ 100% Money Back Guarantee
- ★ 365 Days Free Update
- ★ Instant Download After Purchase
- ★ 24x7 Customer Support
- ★ Average 99.9% Success Rate
- ★ More than 69,000 Satisfied Customers Worldwide
- ★ Multi-Platform capabilities Windows, Mac, Android, iPhone, iPod, iPad, Kindle

Need Help

Please provide as much detail as possible so we can best assist you. To update a previously submitted ticket:

100%



One Year Free Update Free update is available within One Year after your purchase. After One Year, you will get 50% discounts for updating. And we are proud to boast a 24/7 efficient Customer Support system via Email. Money Back Guarantee To ensure that you are spending on quality products, we provide 100% money back guarantee for 30 days from the date of purchase.



We respect customer privacy. We use McAfee's security service to provide you with utmost security for your personal information & peace of mind.

Security & Privacy

Guarantee & Policy | Privacy & Policy | Terms & Conditions

Any charges made through this site will appear as Global Simulators Limited. All trademarks are the property of their respective owners.

Copyright © 2004-2015, All Rights Reserved.