**Exam** : **EE0-426** 

Title : Packeteer Certified

**Specialist** 

Version : DEMO

1. What criteria can be specified in a matching rule? (Choose THREE)
A. SSL URL
B. Set shaping Off C.
Diffserv marking D.
Set discovery On
E. VLAN identification
F. Application-specific criteria
Answer: CEF
2. What type of control features can be configured for folders?
A. Policies
B. Partitions
C. Policy Inheritance
D. Traffic Discovery within Class
Answer: B
3. What can a policy be applied to?
A. folder classes
B. class with children
C. class with no children
D. any class on the class tree
Answer: C
4. What best defines the functionality of Link State Mirroring?
A. PacketShaper will bring down the second port of a NIC pair if the first goes down.
B. PacketShaper mirrors data from an active interface set to a selected port to allow an external analyzer
to be connected to take a packet trace.
C. PacketShaper duplicates data from an active interface and sends out the mirror port to the partner
PacketShaper configured as the hot standby partner.
D. PacketShaper duplicates data from an active interface and sends out the mirror port to the partner

PacketShaper configured as the direct standby partner. Answer: A 5. What is the purpose of configuring direct standby? A. to configure PacketShapers in one-armed mode B. to monitor a connected router's WAN interface(s) C. to configure PacketShapers in a redundant topology D. to configure PacketShapers to participate in routing decisions Answer: C 6. What best describes the capabilities available as part of the Packeteer unit high availability feature? (Choose TWO) A. traffic discovery B. automatic data back-up C. non-inline traffic monitoring D. automatic link capacity adjustment E. insertion in redundant network topologies Answer: DE 7. Why would the Failover feature in Setup be configured? A. to detect if a Frame Relay PVC has failed and to adjust the link speed as appropriate B. to detect if a site router's primary link has failed and to adjust the link speed as appropriate C. to detect if a site router has failed and to configure a new site router IP address and link speed D. to detect if a WAN router has become unavailable and to djust the total link speed as appropriate Answer: B 8. Using the exhibit provided, what PacketShaper feature can be enabled to ensure an Ethernet switch that forms a branch office LAN is able to detect if the router fails?



- A. Failover
- B. Bypass mode
- C. Link-State Mirroring
- D. Bridge Pass-through

Answer: C

- 9. What class will automatically be at the highest point in the tree?
- A. NetBIOS-IP
- B. The Default bucket
- C. TCP Discovered\_Port\_123
- D. Any class with an IP address
- E. HTTP which was auto-discovered

Answer: D

- 10. What is the correct procedure to install a LAN Expansion Module in a PacketShaper for enabling direct standby?
- A. Install in the lowest slot and use the inside port.
- B. Install in the lowest slot and use the outside port.
- C. Install in the most upper slot and use the inside port.
- D. Install in the most upper slot and use the outside port.

Answer: D

## **Trying our product!**

- ★ 100% Guaranteed Success
- ★ 100% Money Back Guarantee
- ★ 365 Days Free Update
- ★ Instant Download After Purchase
- ★ 24x7 Customer Support
- ★ Average 99.9% Success Rate
- ★ More than 69,000 Satisfied Customers Worldwide
- ★ Multi-Platform capabilities Windows, Mac, Android, iPhone, iPod, iPad, Kindle

## **Need Help**

Please provide as much detail as possible so we can best assist you.

To update a previously submitted ticket:





## Guarantee & Policy | Privacy & Policy | Terms & Conditions

Any charges made through this site will appear as Global Simulators Limited.

All trademarks are the property of their respective owners.

Copyright © 2004-2014, All Rights Reserved.