

Vendor: Extreme Networks

Exam Code: EW0-300

Exam Name: Extreme Networks Specialist....

Version:Demo

QUESTION 1

Which of the following IP destination addresses can be used for multicast streams?

A. 10.1.0.0

B. 226.0.0.1

C. 192.168.10.0

D. 172.18.255.255

Correct Answer: B

QUESTION 2

In normal operation the master node in the EAPS ring blocks the secondary port for all non-control traffic belonging to the EAPS domain.

A. TRUE

B. FALSE

Correct Answer: A

QUESTION 3

Although you can specify sequence numbers for different ACL entries, the Summit 1i switch checks incoming traffic on a match with the ACL entries in the order of their time in configuration

A. TRUE

B. FALSE

Correct Answer: B

QUESTION 4

The default OSPF router dead interval for Extreme Networks switches is

A. 10 seconds

B. 40 seconds

C. 120 seconds

D. 180 seconds

Correct Answer: B

QUESTION 5

What does the abbreviation PIM stands for?

- A. Protocol Implicit Multicast
- B. Protocol Independent Multicast
- C. Port Independent Multicast
- D. Port Implicit Multicast

Correct Answer: B

QUESTION 6

Select the correct statements related to IP Multicast?

- A. IP multicast uses unreliable data transfer protocol as UDP
- B. The network must be IP multicast enabled
- C. IP Multicast routers must maintain state information of active multicast groups
- D. All of the above

Correct Answer: D

QUESTION 7

In OSPF, the router type that is required to connect an area with another area is the

- A. Designated Router
- B. Back-up Designated Router
- C. ASBR
- D. ABR

Correct Answer: D

QUESTION 8

The following MAC address, 00.00.5E 00.01.0A represents

- A. The MAC address used for ESRP, instance 01
- B. The MAC address used for ESRP, instance 10

- C. The MAC address used for VRRP, instance 01 D. The MAC address used for VRRP, instance 10 Correct Answer: D **QUESTION 9** Select the statements that apply when you compare and differentiate VRRP and ESRP. A. VRRP does not use the number of active ports as a criteria for Master election B. VRRP can be enabled on VLAN default C. VRRP and Spanning Tree can be enabled on the same switch and VLAN D. All of the above Correct Answer: D **QUESTION 10** Radius on Extreme Networks IS? Chipset switches allows validation for the following switch access methods A. Telnet B. VISTA C. Console D. All of the above Correct Answer: D **QUESTION 11** Is it possible to create multicast STPD on a switch? A. No
- B. Yes, but only if all ports are in the same STP mode
- C. Yes, but only if all ports are in 802.1D mode
- D. Yes, but overlapping ports may not be in 802.1D mode for more then one STPD.

Correct Answer: D

QUESTION 12

What is the RP-set?

A. It is the information of which RP are available for what Multicast groups. It is send by the BSR towards all PIM routers

B. It is the information of which multicast groups are activelt is send by the RP towards all PIM routers

C. It is the information of which BSR are available for what Multicast groups. It is send by RP towards all PIM routers

D. It is the information, stored by all RP, needed to find the BSR,

Correct Answer: A